

8X Super slim DVD Multi Writer LF: AD-7913A

Read speed: 8x max. DVD and 24x max. CD

Write speed:

DVD+R:	8x max.	DVD-R:	8x max.
DVD+RW:	8x max.	DVD-RW:	6x max.
DVD+R9:	4x max.	DVD-R DL:	4x max.
		DVD-RAM:	5x max.
CD-R:	24x max.	CD-RW:	16x max.

Labelflash™ laser labeling system

IDE/ATAPI interface with UltraDMA 33

(max. 33 MByte/sec transfer rate)

12cm and 8cm CD and DVD media supported

0.15 kg weight

Emergency eject



Specifications	8x super slim DVD Multi Writer Labelflash™ (AD-7913A)	
	DVD	CD
Transfer Rate read (max.)	8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
Transfer Rate write	-R 8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
	-R DL 4x ZCLV (max. 5500 kByte/s)	. /
	-RW 6x ZCLV (max. 8250 kByte/s)	16x ZCLV (max. 2400 kByte/s)
	-RAM 5x ZCLV (max. 6900 kByte/s)	. /
	+R 8x ZCLV (max. 11000 kByte/s)	. /
	+R9 4x ZCLV (max. 5500 kByte/s)	. /
	+RW 8x ZCLV (max. 11000 kByte/s)	. /
Access Time	180 ms	150 ms
Mechanism	Tray load mechanism	
Interface	IDE / ATAPI	
Burst Transfer Rate	PIO mode 4 / Ultra DMA 33	
Cache Memory	2 MByte	
Media/Modes supported	DVD-ROM, DVD-R(DL), DVD-RW, DVD+R(9), DVD+RW, DVD-Video, CD-ROM, CD-ROM XA, CD-Audio, CD Extra, CD Text, CD-I Ready, CD-Bridge, Photo-CD, VideoCD, Hybrid CD, Labelflash™	
Writing methods	DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession	
Compatibility	MPC Level 3, MultiRead, PC2001	
Weight	0.15 kg	
Dimensions	128mm x 9.5mm x 129mm	